

LISTING APPROVAL

The DecoShield® Cover Support System is a patented modular system and is UL-Listed as a decorative cover support system intended to be used with UL-Listed thermoplastic sprinkler piping, such as the BlazeMaster® CPVC piping system.

The DecoShield® product is to be installed only in accordance with the approved applications of NFPA 13 – Light Hazard, NFPA 13R and NFPA 13D for CPVC pipe. The DecoShield® System is also subject to the limitations approved for exposed bare CPVC pipe, i.e., smooth, flat, horizontal ceiling construction with Listed quick response or residential sprinkler.

The DecoShield®-M System is designed for use with metal pipe and is UL-Listed as a decorative cover system with sprinkler piping. When using the DecoShield-M System, the compatible metal "Hugger" pipe hanger is utilized to support the piping system.

The DecoShield® Cover is manufactured from an engineered low flame spread; low smoke generation thermoplastic designed for interior finish construction applications, as well as for exterior applications. As used in the DecoShield® Cover, the compound has a flame spread index of less than 20 and a smoke developed index of less than 250. These ratings comply with most model code requirements for Class A (or 1) interior finish. The material is classified by Underwriters Laboratories and is referenced in the UL Building Materials Directory under the category "Molded Plastics" (BTAT – File R10380).

10 – YEAR, LIMITED WARRANTY

DecoShield® Systems, Inc. warrants that DecoShield® products are free of material and workmanship defects for a period of ten (10) years from the delivery date of the products and that DecoShield® Systems, Inc. will replace any defective products without charge provided DecoShield® Systems, Inc. and/or their authorized agent is given the prior opportunity to inspect any alleged defective product and to examine the installation and use thereof.

Except as set forth herein, DecoShield® Systems, Inc. makes no representations or warranties, express or implied, of any kind or nature, including but not limited to any representation or warranties that DecoShield® products are merchantable or fit for any particular purpose. The warranty set forth herein does not apply to and under no circumstance will DecoShield® Systems, Inc. be liable for any incidental, indirect, special or consequential damage, loss, penalty, or expense of any kind including, but not limited to, any expenses incurred for product removal or re-installation. DecoShield® Systems, Inc. will not be liable for any damage to or defect in any DecoShield® product which has been subject to misuse, neglect or accident or which has been stored, used or installed in violation of recommended installation or maintenance procedures.

DISCLAIMER

Although general installation procedures and guidelines literature are provided for the DecoShield® modular retrofit system said procedures and guidelines were developed with laboratory installations and testing. Field conditions may differ. DecoShield® Systems, Inc. is not a piping design engineer. Installer is invited to use his own judgment when installing the DecoShield® System according to field conditions and, if necessary in installer's opinion, to consult with, at his own expense, qualified experts or consultants.

DecoShield® Systems, Inc.'s delivery dates are estimates. DecoShield® Systems uses its best efforts to meet such dates. HOWEVER, DECOSHIELD® SYSTEMS, INC. DISCLAIMS LIABILITY FOR CONSEQUENTIAL DAMAGES FROM LATE DELIVERIES UNLESS DECOSHIELD® SYSTEMS, INC. ASSUMES LIABILITY FOR SUCH DAMAGES IN WRITING WHEN ORDER IS PLACED.

DecoShield® Systems, Inc.
1500 NW 3rd Street, #105, Deerfield Beach, FL 33442
Tel: (800) 873-0894 / (954) 725-7665
Fax: (800) 585-3894 / (954) 725-5993